



## KX-UT Series **SIP Telephones**

- HD Voice and PoE Enabled
- Two Data Ports\* for Simplified Wiring and Connecting a Second Device
- Certified for Use with BroadSoft® BroadWorks® and Digium® Asterisk®
- Environmentally Friendly—Power Consumption 1W in ECO Mode
- Two-year Limited Warranty

\*Select models.





## KX-UT Series **SIP Telephones**

- HD Voice and PoE Enabled
- Two Data Ports\* for Simplified Wiring and Connecting a Second Device
- Certified for Use with BroadSoft® BroadWorks® and Digium® Asterisk®
- Environmentally Friendly—Power Consumption 1W in ECO Mode
- Two-year Limited Warranty





\*Select models.



## The Panasonic SIP Phone UT Series

The new UT Series combines state-of-the-art telephony architecture with business-friendly features. Choose from entry-level models with large, clear LCDs and conferencing capability to executive desk terminals with 6-line displays and wireless headset compatibility. Designed to yield **low total cost of ownership**, UT Series phones are PoE enabled and include extra data ports so there's less wiring expense. An energy-saving Eco Mode feature lets you reduce power consumption while a powerful two-year limited warranty protects your investment well into the life of the phone.

### KX-UT Series Specifications

	 <b>KX-UT136-B</b>	 <b>KX-UT133-B</b>	 <b>KX-UT123-B</b>	 <b>KX-UT113-B</b>
<b>LCD Display</b>	Monochrome Graphical			
<b>LCD Size</b>	242 x 109 pix. – 6 lines	242 x 55 pixels – 3 lines		
<b>LCD Contrast</b>	6 levels			
<b>LCD Backlight</b>	On/Auto/Off			None
<b>INSTALL OPTIONS</b>				
<b>Desk Mount Tilt</b>	Yes - 2 Positions		No	
<b>Wall Mount</b>	KX-A433-B (optional)		KX-A432-B (optional)	
<b>Power Adaptor</b>	KX-A239 (optional)			
<b>NETWORKING</b>				
<b>Ethernet Ports</b>	2 – 10/100			1 – 10/100
<b>Power Over Ethernet (PoE)</b>	Yes (Class 2)			
<b>AUDIO FEATURES</b>				
<b>Audio Codec</b>	G.711, G.722, G.726, G.729a			
<b>Handset, Speaker, Headset Volume</b>	8 levels (includes echo cancellation and distortion prevention) 15 levels			
<b>Ringtones</b>	27			
<b>Ringer Volume</b>	6 levels + Off			
<b>Headset Port</b>	2.5 mm			
<b>Electronic Hook Switch Control Port</b>	3.5mm Plantronics compatible		None	
<b>Hearing Aid</b>	Compatible with Hearing Aid TIA-8013			
<b>KEYS</b>				
<b>Keys (total*)</b>	52		28	
<b>FF Keys</b>	24		-	
<b>Navigator &amp; Cancel Key</b>	Yes			
<b>SOFTWARE FEATURES</b>				
<b>Phone Book Entries</b>	500 - each with 5 numbers			100 - each with 5 numbers
<b>Call Log Entries</b>	30 incoming calls + 30 outgoing calls			
<b>Conferencing</b>	3 parties (within terminal – multi-party dependent on server)			
<b>IP FEATURES</b>				
<b>SIP Accounts</b>	4		2	
<b>SIP Compatibility</b>	RFC 3261 Standard SIP Server, Asterisk®, BroadSoft®			
<b>IP Version</b>	IPv4			
<b>DHCP Client</b>	Yes			
<b>DNS</b>	Yes			
<b>HTTP/HTTPS</b>	Yes			
<b>SNTP Client</b>	Yes			
<b>VLAN (802.1q)</b>	Yes			
<b>QoS (DiffServ)</b>	Yes			
<b>CONFIGURATION</b>				
<b>Plug &amp; Play Configuration</b>	Server based configuration, TR-069, BroadSoft® Device Management Server			
<b>Manual Configuration</b>	Internal web Configurator, Local (LCD based) network configuration			

\*52 keys include 24 keys, 12 dial keys, 4 soft keys and 12 feature keys. Feature keys include 2 navigation keys (direction and center key).

Panasonic System Networks Company of America

**Home & Business Communications**

Three Panasonic Way,  
Secaucus, NJ 07094  
(201) 348 - 7000  
[www.panasonic.com/sip](http://www.panasonic.com/sip)

Design and specifications subject  
to change without notice.

SIP11129SS